

# » KISS 2U V2 PCI 761 «



## 2U Open Solution

- » Noise <35 dBa
- » Shock protected Drive bays
- » i3, i5, i7 1st Generation
- » RAID Subsystem KISS-Stor

## KISS 2U V2 PCI 761

### Kontron Industrial Silent Server

The main attraction of KISS servers is their extremely low noise level, which is inaudible against normal conversation. KISS IPC servers are thus ideal for most noise-sensitive environments such as hospital operating theaters and computers server rooms.

The performance and maximum configuration of KISS servers are based on Kontron's extensive range of CPU boards and backplanes, which allows KISS

systems have been designed for continuous operation and they are to be available for at least the next five years.


In addition to being CE certified, they are also suitable for integration in systems that require UL certification. The specified shock resistance is 15g for 11ms measured along six axes and the MTBF is 50,000 hours.

#### Technical Information


<b>System</b>	KISS 2U V2 PCI 761
<b>Product Line</b>	KISS 2U V2
<b>Dimension (H x W x D)</b>	88 x 482 x 472 mm (2U x 19" x 18.58")
<b>Weight</b>	Approx. 8 kg
<b>Front I/O</b>	2x USB 2.0
<b>Rear I/O</b>	2x LAN 10/100/1000, 1x VGA, 2x COM, 2x USB
<b>Controls on the frontside</b>	Power button
<b>Accessible drive bays</b>	1x 5.25", 1x 3.5"
<b>Internal drive bays</b>	1x 3.5"
<b>Power supply</b>	AC 400 W 80+, optional: AC Redundant, DC 24 V, DC 48 V
<b>Expansion slots</b>	3x PCI 32 Bit, 1x PCI-e x16, 1x PCI-e x4 or 4x PCI-e x4, 1x PCI-e x16
<b>Chipset</b>	Q57
<b>CPU Board</b>	PCI 761
<b>Memory</b>	Up to 8 GB DDR 3
<b>Processor</b>	i3-540, i5-660, i7-860
<b>Cooling</b>	Two hot swap chassis fans, air filter
<b>Temperature</b>	
Non-operating	-20°C to + 70°C (-4°F - 154°F)
Operating	0°C to + 50°C (32°F - 122°F)
<b>Humidity</b>	
Operating/non operating	10-95 % rel humidity at 40 C° non condensing
<b>Shock</b>	
Operating	15g, 11ms
<b>Vibration</b>	
Operating	10-500 Hz, 1g
<b>Noise</b>	< 35 dBA
<b>Approvals</b>	CE, designed to meets UL
<b>Protection Class</b>	IP 20 optional IP 52
<b>Options</b>	DVD RW, KISS DA135, KISS DA425, KISS StorSlim, PCCM

## KISS 2U V2 PCI 761

Kontron Industrial Silent Server



1	19" handle bracket
2	Air grille on the front access panel
3	Securing lock mechanism
4	HDD and Power LED indicators
5	Buffer for the front access panel
6	Fan slide-in module with knurled screws
7	Filter mat and filter mat holder with knurled screws
8	Slot for the locking mechanism
9	Cover fastening screw on the front side
10	Power button
11	D1: 5.25" drive bay
12	D2: front accessible 5.25" slim or internal 3.5" drive bay
13	2x USB 2.0 interfaces at the front side



14	Free slots for expansion cards
15	Grounding stud
16	AC PSU with "On/Off" switch and AC input connector
17	2x serial interfaces (RS232)
18	VGA interface
19	2x USB 2.0 interfaces at the rear side
20	LAN2 interface (RJ45)
21	LAN1 interface (RJ45)
22	Optional: redundant PSU

## CORPORATE OFFICES

### Europe, Middle East & Africa

Lise-Meitner-Str. 3-5  
86156 Augsburg  
Germany

Tel.: +49 (0) 821 4086-0  
Fax: +49 (0) 821 4086 111  
sales@kontron.com

### North America

14118 Stowe Drive  
Poway, CA 92064-7147  
USA

Tel.: +1 888 294 4558  
Fax: +1 858 677 0898  
info@us.kontron.com

### Asia Pacific

17 Building,Block #1, ABP.  
188 Southern West 4th Ring Road  
Beijing 100070, P.R.China

Tel.: +86 10 63751188  
Fax: +86 10 83682438  
info@kontron.cn