



KISS 4U V2 Systems

Configuration Guides

This page is intentionally left blank.

Configuration Options for KISS 4U V2 with PCI 759 SBC			
Categories	Select one option of each category		
Backplane			
	1* PICMG1.0, 4* 32 Bit PCI Full size, 3* PCI Half size, 7* ISA Full size		
	2* PICMG1.0, 8* 32 Bit PCI Full size, 3* PCI Half size, 1* ISA/PCI Shared Full size		
	Others on request		
PICMG Board			
	PCI 759		
Processors			
	Core™ 2 Duo E4300 (1.8GHz)		
	Core™ 2 Duo 6400 (2.13GHz)		
Memory			
	2GB DDR2		
	4GB DDR2		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply			
	AC 400 W 80+		
	AC 650 W 80 +		
	AC Redundant (2* 500W)		
Graphic Adapter			
	No		
	PCI MATROX G550DH 32MB LP DVI		
Network Adapter			
	No		
	PCI NET D-LINK DFE-528TX 10/100Mbps		
Options			
	No		
	Custom Color		
	Slide Rails		
	others on request		
Preinstalled OS			
	No		
	Windows XP		
	Linux Suse		
	Others on request		
Mounting			
	Tower		
	Desktop		
	19" Rack Mount		
Protection Class			
	Front: IP20		
	Front: IP52		

Configuration Options for KISS 4U V2 with PCI 760 SBC			
Categories	Select one option of each category		
Backplane	1* PICMG1.3, 7* 32 Bit PCI Full size, 4* PCIe *1, 1* PCIe *16		
	1* PICMG1.3, 3* 32 Bit PCI Full size, 4* PCIe *1, 4* PCIe *4, 1* PCIe *16		
	Others on request		
PICMG Board	PCI 760		
Processors	Core™ 2 Duo E4300 (1.8GHz)		
	Core™ 2 Duo E8400 (2.13GHz)		
	Core™ 2 Quad Q9400 (2.66GHz)		
Memory	4GB DDR2		
	8GB DDR2		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA435 (4* 500GB) blocks three 5.25" bays		
KISS DA435 (4* 1TB) blocks three 5.25" bays			
KISS DA435 (4* 2TB) blocks three 5.25" bays			
DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay			
DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay			
other drive combinations on request			
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
	others on request		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply	AC 400 W 80+		
	AC 650W 80 +		
	AC Redundant (2* 500W)		
Graphic Adapter	No		
	PCIe *16, NVS 300, 2* DisplayPort incl. 2* Adapter to DVI, passive cooled		
Network Adapter	No		
	PCIe *1 NET SK-9E21D Gigabit LAN		
RAID Controller	No		
	RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14		
Options	No		
	Custom Color		
	3rd LAN onboard on Slot bracket rear		
	Slide Rails		
	PCCM		
	others on request		
Preinstalled OS	No		
	Windows XP		
	Linux Suse		
	WINDOWS 7 Pro 32 Bit		
	Windows 7 Ultimate 64 Bit		
	Others on request		
Mounting	Tower		
	Desktop		
	19" Rack Mount		
Protection Class	Front: IP20		
	Front: IP52		

Configuration Options for KISS 4U V2 with PCI-761 SBC			
Categories	Select one option of each category		
Backplane	1* PICMG1.3, 7* 32 Bit PCI Full size, 4* PCIe *1, 1* PCIe *16		
	1* PICMG1.3, 3* 32 Bit PCI Full size, 4* PCIe *1, 4* PCIe *4, 1* PCIe *16		
PICMG Board	PCI 761		
Processors	Intel i3-540 (3.06GHz)		
	Intel i5 660 (3.33GHz)		
	Intel i7 860 (2.8 GHz) no graphics on board		
Memory	4GB DDR3		
	8GB DDR3		
	16 GB DDR3		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA435 (4* 500GB) blocks three 5.25" bays		
	KISS DA435 (4* 1TB) blocks three 5.25" bays		
	KISS DA435 (4* 2TB) blocks three 5.25" bays		
	DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay		
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply	AC 400 W 80+		
	AC 650W 80 +		
	AC Redundant (2* 500W)		
Graphic Adapter	No		
	PCIe *16 NVS 300, 2* DisplayPort incl. 2* Adapter to DVI, passive cooled		
Network Adapter	No		
	PCIe *1 NET SK-9E21D Gigabit LAN		
RAID Controller	No		
	RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14		
Options	No		
	Custom Color		
	Slide Rails		
	others on request		
Preinstalled OS	No		
	Windows XP		
	Linux Suse		
	WINDOWS 7 Pro 32 Bit		
	Windows 7 Ultimate 64 Bit		
	Others on request		
Mounting	Tower		
	Desktop		
	19" Rack Mount		
Protection Class	Front: IP20		
	Front: IP52		

Configuration Options for KISS 4U with PCI 762			
Categories	Select one option of each category		
Backplane	1* PICMG1.3, 7* 32 Bit PCI Full size, 4* PCIe *1, 1* PCIe *16		
	1* PICMG1.3, 3* 32 Bit PCI Full size, 4* PCIe *1, 4* PCIe *4, 1* PCIe *16		
PICMG Board	PCI 762		
Processors	Intel i3-3220 (3,3GHz)		
	Intel i5-3550S (3,0GHz)		
	Intel i7-3770 (3,4GHz)		
Memory	4GB DDR3		
	8GB DDR3		
	16 GB DDR3		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	DVD-R/RW SATA		
	KISS Stor 0/1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/1 (Blocks two 5.25" bays) no RAID controller required (2* 4TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA335 (3* 4TB) blocks two 5.25" bays		
	KISS DA435 (4* 1TB) blocks three 5.25" bays		
	KISS DA435 (4* 2TB) blocks three 5.25" bays		
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5,25" bay		
	DA 425 (4* 2.5" HDD 1TB GB) blocks one 5,25" bay		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
Power Supply	AC 400 W 80+		
	others on request		
Graphic Adapter	No		
	PCIe *16 NVS300, passive cooled		
Network Adapter	No		
	1* GB LAN (INTEL LAN EXP19301C)		
RAID Controller	No		
	RAID Controller PCIe *4 (RAID 0,1,5,10,JBOD) B14		
Options	No		
	Custom Color		
	Slide Rails		
	others on request		
Preinstalled OS	No		
	Windows XP		
	Linux Suse		
	WINDOWS 7 Pro 32 Bit		
	Windows 7 Ultimate 64 Bit		
	Others on request		
Mounting	Desktop		
	19" Rack Mount		

Configuration Options for KISS 4U V2 with KTQ45 Mainboard				
Categories	Select one option of each category			
Mainboard	KTQ45 ATXE			
Processors	Core™ 2 Duo E8400 (2.13GHz)			
	Core™ 2 Quad Q9400 (2.66GHz)			
Memory	4GB DDR3			
	8GB DDR3			
Drive Bay 1, 2, 3		1	2	3
Front accessible 5.25"	No			
	KISS DA135 500GB			
	KISS DA135 1TB			
	KISS DA135 2TB			
	DVD-R/RW SATA			
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)			
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)			
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)			
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)			
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)			
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)			
	KISS DA335 (3* 500GB) blocks two 5.25" bays			
	KISS DA335 (3* 1TB) blocks two 5.25" bays			
	KISS DA335 (3* 2TB) blocks two 5.25" bays			
	KISS DA435 (4* 500GB) blocks three 5.25" bays			
	KISS DA435 (4* 1TB) blocks three 5.25" bays			
	KISS DA435 (4* 2TB) blocks three 5.25" bays			
	DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay			
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay			
	other drive combinations on request			
Drive Bay 4		4		
Internal 3.5"	No			
	SATA 500 GB			
	SATA 1 TB			
	SATA 2 TB			
	1* 2,5" HDD 250 GB			
	1* 2.5" HDD 500 GB			
	SSD 64 GB SLC			
	SSD 128 GB MLC			
	Slim-line RW DVD (front accessible)			
Drive Bay 5		5		
Front accessible 3.5"	No			
	CF Reader 1* 4 GB CF			
	CF Reader 1* 8 GB CF			
	CF Reader 1* 16 GB CF			
	others on request			
Power Supply				
	AC 400 W 80+			
	AC 650W 80 +			
	AC Redundant (2* 500W)			
Graphic Adapter				
	No			
	PCIe *16 NVS 300, 2* Display port incl. 2* Adapter to DVI, passive cooled			
Network Adapter				
	No			
	PCIe *1 NET SK-9E21D Gigabit LAN			
RAID Controller				
	No			
	RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14			
Options				
	No			
	Custom Color			
	EASY 485/422 adapter (non galvanic isolated)			
	Slide Rails			
	others on request			
Preinstalled OS				
	No			
	Windows XP			
	Linux Suse			
	WINDOWS 7 Pro 32 Bit			
	Windows 7 Ultimate 64 Bit			
	Others on request			
Mounting				
	Tower			
	Desktop			
	19" Rack Mount			
Protection Class				
	Front: IP20			
	Front: IP52			

Configuration Options for KISS 4U V2 with Q57 ATX Mainboard			
Categories	Select one option of each category		
Mainboard	Q57 ATX		
Processors	Intel i3-540 (3.06GHz)		
	Intel i5 660 (3.33GHz)		
	Intel i7 860 (2.8 GHZ) no graphics on board		
Memory	4GB DDR3		
	8GB DDR3		
	16GB DDR3		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA435 (4* 500GB) blocks three 5.25" bays		
	KISS DA435 (4* 1TB) blocks three 5.25" bays		
	KISS DA435 (4* 2TB) blocks three 5.25" bays		
	DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay		
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay		
	other drive combinations on request		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply	AC 400 W 80+		
	AC 650W 80 +		
	AC Redundant (2* 500W)		
Graphic Adapter	No		
	PCIe *16 NVS 300, 2* Display port incl. 2* Adapter to DVI, passive cooled		
Network Adapter	No		
	PCIe *1 NET SK-9E21D Gigabit LAN		
RAID Controller	No		
	RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14		
Options	No		
	Custom Color		
	Slide Rails		
	others on request		
Preinstalled OS	No		
	Windows XP		
	Linux Suse		
	WINDOWS 7 Pro 32 Bit		
	Windows 7 Ultimate 64 Bit		
	Others on request		
Mounting	Tower		
	Desktop		
	19" Rack Mount		
Protection Class	Front: IP20		
	Front: IP52		

Configuration Options for KISS 4U V2 with Q67 ATX Mainboard			
Categories	Select one option of each category		
Mainboard	KTQ67 ATXE		
Processors	Intel i3-2120 3.3GHz		
	Intel i5-2400 3.1GHz		
	Intel i7-2600 3.4GHz		
Memory	4GB DDR3		
	8GB DDR3		
	16 GB DDR3		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA435 (4* 500GB) blocks three 5.25" bays		
	KISS DA435 (4* 1TB) blocks three 5.25" bays		
	KISS DA435 (4* 2TB) blocks three 5.25" bays		
	DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay		
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay		
	other drive combinations on request		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply	AC 400 W 80+		
	AC 650W 80 +		
	AC Redundant (2* 500W)		
Graphic Adapter	No		
	PCIe *16 NVS 300, 2* Display port incl. 2* Adapter to DVI, passive cooled		
Network Adapter	No		
	PCIe *1 NET SK-9E21D Gigabit LAN		
RAID Controller	No		
	RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14		
Options	No		
	Custom Color		
	Slide Rails		
	others on request		
Preinstalled OS	No		
	Windows XP		
	Linux Suse		
	WINDOWS 7 Pro 32 Bit		
	Windows 7 Ultimate 64 Bit		
	Others on request		
Mounting	Tower		
	Desktop		
	19" Rack Mount		
Protection Class	Front: IP20		
	Front: IP52		

Configuration Option for KISS 4U V2 X9SCA-F			
Categories	Select one of each category		
Mainboard	X9SCA-F ATX		
Expansion Slots	2* PCIe x4 (as PCIe x8 slots), 1* PCIe x16, 3* PCI 32 bit		
Processor	Intel® Xeon® E3-1275 (8M Cache, 3.40 GHz) Intel® Xeon® E3-1225 (6M Cache, 3.10 GHz)		
Memory	8GB DDR3 ECC 16GB DDR3 ECC 32GB DDR3 ECC		
Drive Bay 1, 2, 3		1	2 3
Front accessible 5.25"	No		
	KISS DA135 500GB		
	KISS DA135 1TB		
	KISS DA135 2TB		
	DVD-R/RW SATA		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 500 GB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 1TB SATA WD)		
	KISS Stor 1 (Blocks two 5.25" bays) no RAID controller required (2* 2TB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3* 500 GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*1TB GB SATA WD)		
	KISS Stor 0/5 (Blocks two 5.25" bays) no RAID controller required (3*2TB SATA WD)		
	KISS DA335 (3* 500GB) blocks two 5.25" bays		
	KISS DA335 (3* 1TB) blocks two 5.25" bays		
	KISS DA335 (3* 2TB) blocks two 5.25" bays		
	KISS DA435 (4* 500GB) blocks three 5.25" bays		
	KISS DA435 (4* 1TB) blocks three 5.25" bays		
	KISS DA435 (4* 2TB) blocks three 5.25" bays		
	DA 425 (4* 2.5" HDD 250 GB) blocks one 5.25" bay		
	DA 425 (4* 2.5" HDD 500 GB) blocks one 5.25" bay		
	other drive combinations on request		
Drive Bay 4		4	
Internal 3.5"	No		
	SATA 500 GB		
	SATA 1 TB		
	SATA 2 TB		
	1* 2.5" HDD 250 GB		
	1* 2.5" HDD 500 GB		
	SSD 64 GB SLC		
	SSD 128 GB MLC		
	Slim-line RW DVD (front accessible)		
Drive Bay 5		5	
Front accessible 3.5"	No		
	CF Reader 1* 4 GB CF		
	CF Reader 1* 8 GB CF		
	CF Reader 1* 16 GB CF		
	others on request		
Power Supply	AC 400 W 80+ AC 650W 80 + AC Redundant (2* 500W)		
Graphic Adapter	No PCIe *16 NVS 300, 2* Display port incl. 2* Adapter to DVI, passive cooled		
Network Adapter	No PCIe *1 NET SK-9E21D Gigabit LAN		
RAID Controller	No RAID Controller PCIe *4 (RAID 0, 1, 5, 10, JBOD) B14		
Options	No Custom Color Slide Rails others on request		
Preinstalled OS	No Windows XP Linux Suse WINDOWS 7 Pro 32 Bit Windows 7 Ultimate 64 Bit Others on request		
Mounting	Tower Desktop 19" Rack Mount		
Protection Class	Front: IP20 Front: IP52		